




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04Q 7/28		A2	(11) International Publication Number: WO 97/50266
			(43) International Publication Date: 31 December 1997 (31.12.97)
(21) International Application Number: PCT/US97/10831		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 23 June 1997 (23.06.97)			
(30) Priority Data: 669,778 26 June 1996 (26.06.96) US			
(71) Applicant: QUALCOMM INCORPORATED [US/US]; 6455 Lusk Boulevard, San Diego, CA 92121 (US).			
(72) Inventors: YAO, Yu-Dong; 10923 Caminito Alvarez, San Diego, CA 92126 (US). GROB, Matthew, S.; 2757 Bordeaux Avenue, La Jolla, CA 92037 (US).			
(74) Agent: OGROD, Gregory, D.; Qualcomm Incorporated, 6455 Lusk Boulevard, San Diego, CA 92121 (US).			
		Published Without international search report and to be republished upon receipt of that report.	

(54) Title: METHOD AND APPARATUS FOR MONITORING LINK ACTIVITY TO PREVENT SYSTEM DEADLOCK IN A DISPATCH SYSTEM



(57) Abstract

A method and apparatus to prevent system deadlock in a dispatch system by monitoring link activity is described. The dispatch system is comprised of a set of remote units (10, 20, 22) which communicate with each other by broadcasting one at a time to the group. A remote unit (10) communicates with the other remote units through at least one base station (44). A communications manager (40) grants a remote unit (10) to be the exclusive system talker upon request through the base station servicing the requesting remote unit (44). The base station (44) monitors a series of data from the remote unit designated as the system talker (10) to detect voice activity. The base station (44) sends a surrogate request to the communications manager (40) to relinquish the system talker privilege if the voice activity falls below a predetermined threshold.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD AND APPARATUS FOR MONITORING LINK ACTIVITY TO PREVENT SYSTEM DEADLOCK IN A DISPATCH SYSTEM

BACKGROUND OF THE INVENTION

I. Field of the Invention

This invention relates generally to dispatch systems and, more particularly, to the implementation of a dispatch system in a cellular system.

II. Description of the Related Art

In a wireless telephone communication system, many users communicate over a wireless channel to connect to other wireless and wireline telephone systems. Communication over the wireless channel can be one of a variety of multiple access techniques. These multiple access techniques include time division multiple access (TDMA), frequency division multiple access (FDMA), and code division multiple access (CDMA). The CDMA technique has many advantages. An exemplary CDMA system is described in U.S. Patent No. 4,901,307 issued February 13, 1990 to K. Gilhousen et al., entitled "SPREAD SPECTRUM MULTIPLE ACCESS COMMUNICATION SYSTEM USING SATELLITE OR TERRESTRIAL REPEATERS," assigned to the assignee of the present invention and incorporated herein by reference.

In the just mentioned patent, a multiple access technique is disclosed where a large number of mobile telephone system users, each having a transceiver, communicate through satellite repeaters, airborne repeaters, or terrestrial base station transceiver subsystems using CDMA spread spectrum communication signals. In using CDMA communications, the frequency spectrum can be reused multiple times permitting an increase in system user capacity.

In the CDMA cellular system, each base station transceiver subsystem provides coverage to a limited geographic area and links the remote units in its coverage area through a cellular system switch to the public switched telephone network (PSTN). When a remote unit moves to the coverage area of a new base station transceiver subsystem, the routing of that user's call is transferred to the new base station transceiver subsystem. The base station-to-remote unit signal transmission path is referred to as the forward link and the remote unit-to-base station signal transmission path is referred to as the reverse link.

In a typical wireless telephone communication system, the remote unit may employ a vocoding system which encodes voice information in a variable rate format. In a variable rate system, the data rate may be lowered due to pauses in the voice activity. The lower data rate reduces the level of interference to other users caused by the remote unit transmissions. At the base station a vocoding system is employed for reconstructing the voice information. In addition to voice information, data information alone or a mixture of the two may be transmitted by the remote unit.

When a remote unit is producing its own data for transmission, an internal vocoder produces from digital samples of the voice information encoded data at four different rates, e.g. approximately 8,000 bits per second (bps), 4,000 bps, 2,000 bps and 1,000 bps, based on voice activity during a 20 millisecond (ms) frame. Each frame of vocoder data is formatted with overhead bits as 9,600 bps, 4,800 bps, 2,400 bps, and 1,200 bps data frames. The highest rate data frame which corresponds to a 9,600 bps frame is referred to as a "full rate" frame; a 4,800 bps data frame is referred to as a "half rate" frame; a 2,400 bps data frame is referred to as a "quarter rate" frame; and a 1,200 bps data frame is referred to as an "eighth rate" frame. A vocoder which is suited for application in this environment is described in U.S. patent No. 5,414,796, entitled "VARIABLE RATE VOCODER," issued May 9, 1995 and assigned to the assignee of the present invention. When the remote unit receives data from an outside source such as a terminal equipment unit, the remote unit continues to process the data in this variable rate frame format.

When the original cellular telephone spectrum licenses were issued by the government, one of the restrictions on use of the spectrum was that the carriers could not provide dispatch services. However, because of the great advantages of the CDMA system and the inherent expense and problems of deployment and maintenance of private dispatch systems, the government is re-examining this issue. The government itself would benefit greatly from such services.

Whereas typical wireless and wireline telephone service provides point-to-point service, dispatch services provide one-to-many service. Common usage of dispatch services are local police radio systems, taxicab dispatch systems, Federal Bureau of Intelligence and secret service operations, and general military communication systems.

The basic model of a dispatch system consists of a broadcast net of users. Each broadcast net user monitors a common broadcast forward link signal. If a net user wishes to talk, he presses a push-to-talk (PTT) button and he is granted system talker privileges. Typically the talking user's voice is routed

from the reverse link over the broadcast forward link. Ideally the dispatch system allows landline and wireless access to the system. When the remote unit user has finished speaking, he releases the PTT button. In response the remote unit generates a push-to-talk off indication which terminates the privileges and frees the system for use by other system users.

If the push-to-talk button on a remote unit becomes stuck down, the remote unit may be granted system talker privileges. System resources are thus expended and other remote units may be prevented from accessing the system because the remote unit with the stuck push-to-talk button is blocking the system. This type of scenario is referred to as system deadlock and it is, of course, a highly undesirable state. The present invention is a method and apparatus for detecting system deadlock and truncating its deleterious effects.

SUMMARY OF THE INVENTION

When a remote unit user presses the push-to-talk button, a communications manager may grant the remote unit system talker privileges. When the remote unit has system talker privileges, his voice signal is broadcast to the other remote units which are members of the dispatch system. When the remote unit user releases the push-to-talk button, the communications manager denies the remote unit system talker privileges and thus freeing the system for other remote unit to have the system talker privileges. If the remote unit's push-to-talk button becomes stuck down, the remote unit retains system talker privileges thus preventing other remote units from getting a grant of system talker privileges. The present invention monitors the voice activity of the signal received from the remote unit at the base station. If the voice activity falls below a certain level, it is assumed that the remote unit is no longer in need of system talker privileges and the base station generates a surrogate indication that the push-to-talk button has been released which is sent to the communications manager. In this way the communications manager is free to grant system talker privileges to another remote unit.

BRIEF DESCRIPTION OF THE DRAWINGS

The features, objects, and advantages of the present invention will become more apparent from the detailed description set forth below when taken in conjunction with the drawings wherein:

FIG. 1 is a block diagram of a typical dispatch system; and

FIG. 2 is a flow chart showing an exemplary set of steps to implement the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 1 shows a typical dispatch system. In the preferred embodiment, remote units 10, 20, 22, and 24 may function both as dispatch units and as point-to-point telephones. In FIG. 1, remote unit 10 is currently active and remote units 20, 22, and 24 are currently passive listeners. Base station antennas 30, 32, and 34 may provide the broadcast forward link channel to remote units 20, 22, and 24. Base station antenna 30 transmits and receives a dedicated forward and reverse traffic channel to and from remote unit 10. The dedicated traffic channel is similar to the forward link broadcast channel except that, for example, remote unit 10 may receive other remote unit specific signaling information such as power control commands. Mobile switching center (MSC) 38 coordinates the signaling to and from a set of the base station transceiver subsystems comprising base station transceiver subsystems 44, 48, and 50. The system comprising base station antennas 30, 32, and 34, and base station transceiver subsystems 44, 48, and 50 and MSC 38 is referred as base station 28. Communication manager 40 controls the net such as the granting system talker privileges to a remote unit whose user has pressed the 'push-to-talk' (PTT) button. In the preferred embodiment, the air interface signaling and modulation is in accordance with the Code Division Multiple Access (CDMA) system described in "Mobile Station-Base Station Compatibility Standard for Dual-Mode Wideband Spread Spectrum Cellular Systems" TIA/EIA/IS-95, generally referred to simply as IS-95. In IS-95, the remote unit is referred to as a mobile station.

It is well known in the art that base station transceiver subsystems may be sectorized such as into three sectors. Where the term *base station* or *base station transceiver subsystem* is used herein, it is implied that the term may refer to an entire base station transceiver subsystem or to a single sector of a base station transceiver subsystem.

In FIG. 1 active remote unit 10 has an established bidirectional link with base station transceiver subsystem 44. In order to become active, remote unit 10 sends an access channel message requesting a traffic channel to base station transceiver subsystem 44. The access message is sent on the access channel. The access channel is a reverse link channel used by remote units for communicating to the base station. The access channel is a shared slotted random access channel. Only one remote unit per base station transceiver subsystem sector per frequency channel can successfully use the access channel

at one time. The access channel is used for short signaling message exchanges such as call originations, responses to pages, and registration. An access attempt is sent by the remote unit in a series of access probes. Each access probe carries the same information but is transmitted at a higher power level than the previous one. The access probes continue until a base station acknowledgment is received at the remote unit.

When remote unit 10 has established a communication link, it receives any signaling present on the forward broadcast channel on a dedicated forward link traffic channel. In this way, remote unit 10 does not monitor the forward link broadcast channel yet it receives all of the dispatch system information on its own dedicated forward link traffic channel. Remote unit 10 communicates back to base station transceiver subsystem 44 on a dedicated reverse channel. Because remote unit 10 has its own dedicated forward link signal path, remote unit specific messaging may be included in the signaling. For example, if remote unit 10 is capable of operating both as a dispatch system remote unit and as a point-to-point telephone unit, remote unit 10 may be informed on the forward link traffic channel that an incoming point-to-point call is being directed toward remote unit 10.

On the other hand, in FIG. 1, passive remote units 20, 22, and 24 do not have an established reverse link signal to any of the base station transceiver subsystems. Even if remote units 20, 22 and 24 are passive, they still may use the access channel to communicate with the base station. In the preferred embodiment, passive remote units 20, 22 and 24 use the access channel to signal the base station transceiver subsystem if they are in need of more power from the forward link broadcast channel. In response to the power request access message, the base station transceiver subsystem may increase the transmit power level of the forward link broadcast channel.

In a standard CDMA system the process of allocating resources so that the remote unit may become active may take several seconds as well as a substantial amount of processing resources. In order to preserve system resources and to avoid the associated delay, in the preferred embodiment, when a remote unit presses the push-to-talk button, a set of resources is allocated. When the remote unit releases the push-to-talk button, the resources remain dedicated to the remote unit for some period of time. During the time when the user is not depressing the push-to-talk button, the remote unit is designated as active and is said to be hanging. A remote unit which is hanging sends and receives a low rate series of idle messages to preserve the link power control. In this way, when the remote unit user subsequently depresses the push-to-talk button, the link is completely

established and immediately responsive. This type of operation accommodates the natural dialog use of a dispatch system. When the pause between push-to-talk activations exceeds a threshold, the resources may be released. After the resources have been released, the remote unit must send
5 an origination message on an access channel to reestablish a connection. Although it is true that at any one time only one remote unit may be talking, more than one remote unit may be active.

The operation of the system described above may be vastly different than standard push-to-talk operation. A typical push-to-talk system is
10 implemented using a common frequency or set of two frequencies. Once a remote unit user has pressed the push-to-talk button, he is transmitting on the common frequency and has blocked all others from accessing the channel. He also blocks the channel by pressing his push-to-talk button even when another user was speaking first. Typically, while the talker is speaking his
15 receiver is disabled to avoid feedback. In this way, when the remote unit user depresses the push-to-talk button and his receiver is disabled, he will not hear his own voice. Therefore if one unit's push-to-talk button is stuck down, not only can no other user access the system but the user himself may not be able to hear a warning message even if an overriding message is transmitted.

In a standard push-to-talk system there is no request of system talker
20 privileges and a corresponding grant of system talker privileges. Also there is no way to deny system talker privileges after a remote unit has pressed the push-to-talk button. Also in a typical system it is difficult to detect voice activity. The present invention is much different. In the preferred
25 embodiment, a CDMA multiple access technique is used. (In alternative embodiments other multiple access techniques may be used.) In a CDMA system, more than one remote unit may transmit on the same frequency at the same time. Even if the remote unit continually transmits, other remote units in the area remain able to use the same frequency to communicate on
30 the access channel, dedicated traffic channels, and forward link broadcast channel as well as others. Also note that while the remote unit is talking and generating a reverse link traffic channel signal, it continues to receive the forward link traffic channel signal. If the remote unit user's voice is not included in the forward link traffic channel signal, the speaker on the remote
35 unit may remain enabled while the remote unit is designated as the system talker. In this way, a privileged unit could generate a voice message for the remote unit even when his push-to-talk button is depressed.

When the user initially presses the push-to-talk button, a PTT_on indication is sent from the remote unit to the base station. When the user

releases the push-to-talk button, a PTT_off indication is sent from the remote unit to the base station. Nominally, until the PTT_off indication is received, no other user may be granted push-to-talk access. One aspect of the present invention addresses the situation in which a push-to-talk button malfunctions such that no PTT_off indication is transmitted.

In the preferred embodiment, the remote unit comprises a multirate vocoder. A multirate vocoder transmits at a low rate when voice or data activity is minimized and transmits at higher rates when the level voice or data activity is high. In the preferred embodiment, the internal vocoder produces encoded data from digital samples of the voice information at four different rates, e.g. approximately 8,000 bits per second (bps), 4,000 bps, 2,000 bps and 1,000 bps, based on voice activity during a 20 millisecond (ms) frame. Each frame of vocoder data is formatted with overhead bits as 9,600 bps, 4,800 bps, 2,400 bps, and 1,200 bps data frames. The highest rate data frame which corresponds to a 9,600 bps frame is referred to as a "full rate" frame; a 4,800 bps data frame is referred to as a "half rate" frame; a 2,400 bps data frame is referred to as a "quarter rate" frame; and a 1,200 bps data frame is referred to as an "eighth rate" frame. A vocoder which is suited for application in this environment is described in U.S. patent No. 5,414,796, entitled "VARIABLE RATE VOCODER," issued May 9, 1995 and assigned to the assignee of the present invention. Even when the remote unit receives data from an outside source such as a terminal equipment unit, the remote unit continues to process the data in this variable rate frame format. The present invention may make use of the fact that if minimal link data is present, the vocoder sends eighth rate frames.

There are two different scenarios that are addressed by the present invention. In the first scenario, the user presses the push-to-talk button. The remote unit sends a PTT_on indication and receives a channel assignment. However, either intentionally or unexpectedly the user does not speak. Additionally, no PTT_off indication is received at the base station. The base station may not receive the PTT_off indication if the user does not release the push-to-talk button. The base station may not receive the PTT_off indication if the button is stuck on or the remote unit is otherwise malfunctioning.

In a similar but slightly different second scenario, the user presses the push-to-talk button. The remote unit sends a PTT_on indication and receives a channel assignment. The user speaks and sends voice traffic to the other net members. However, either intentionally or unexpectedly the user stops speaking for an extended period of time. Again, no PTT_off indication is received at the base station. The base station may not receive the PTT_off

indication if the user does not release the push-to-talk button. The base station may not receive the PTT_off indication if the button is stuck on or the remote unit is otherwise malfunctioning.

5 In either scenario, unless one of the members of the net has been designated a higher priority user and can 'interrupt' the errant remote unit, the system is in deadlock. In such a case, no other remote unit on the net may become the talker thus disabling the network. The present invention prevents such a deadlock by monitoring the link (voice or data) activity. The present invention may be used in conjunction with other mechanisms to prevent deadlock and to regulate system access such as those described in U.S. Patent Application Serial No. 08/671,132 entitled "METHOD AND APPARATUS FOR ACCESS REGULATION AND SYSTEM PROTECTION OF A DISPATCH SYSTEM" which was filed June 24, 1996 and is assigned to the assignee hereof and in U.S. Patent Application Serial No. 08/671,131 entitled 10 "METHOD AND APPARATUS FOR EFFICIENT SYSTEM ACCESS IN A DISPATCH SYSTEM" which was filed June 24, 1996 and is assigned to the assignee hereof.

There are several ways in which to detect link activity. If a vocoder similar to the one described above is used, the average number of low rate frames received over a period of time may be determined. This method also is applicable to data transmissions. In this way, if background noise causes occasional higher rate frames, the lack of a valid continuous voice signal is still detected. Other fixed rate digital vocoders may use different encoding methods depending on whether the audio signal is voice or non-voice noise. 20 The base station may monitor an indication of the type of encoding used to encode the signal to detect link activity. Another scheme may monitor the spectral content of the encoded signal to determine the presence or absence of voice. The absence of data on data connection may be even easier to detect. For example, the base station may simply look at the number of transitions in the incoming signal or the average number of bits with value '1' as compared to the total number of bits. 30

FIG. 2 is a flow chart with which the basic operation of the present invention is explained. In the preferred embodiment, the system is executed by base station 28 (of FIG. 1). The system most likely resides in MSC 38 (of FIG. 1) while several of the operations may take place within the base station transceiver subsystems. In the most general embodiment, the system may be located in any part of the communications system. The system shown in FIG. 2 is executed once for each remote unit which is granted system talker privileges. 35

From start block 100, operation begins when a grant of system talker privileges is received for the remote unit, block 102. Such a grant is typically in response to a PTT_on indication received from the remote unit. The two counts are set to an initial value also in block 102. As the first data is transferred from the remote unit to the base station, the base station determines whether or not there is sufficient link activity to indicate receipt of an active voice or data communication, block 106. If not, the T_1 count is incremented to reflect the passage of time, block 108. Block 110 asks if a denial of system talker privileges has been received. Such a denial may be received if the remote unit releases the push-to-talk button or if the remote unit is interrupted by another remote unit. If a denial has been received, the flow ends in block 114. If no denial has been received, flow continues to block 112. If the T_1 count does not exceed the threshold, threshold₁, in block 112, the flow continues back to block 106. If the T_1 count exceeds the threshold, threshold₁, in block 112, the base station generates a surrogate PTT_off indication to send to the communications manager, block 134 thereby freeing the system for use by other remote units.

If link activity is detected in block 106, a second phase of the flow chart addressing the second scenario above is entered. As the data continues to be transferred from the remote unit to the base station, block 116 monitors for link activity. If there is not sufficient link activity to indicate receipt of an active voice or data communication, the T_2 count is incremented to reflect the passage of time in block 118. Block 120 asks if a denial of system talker privileges has been received. If a denial has been received, the flow ends in block 128. If no denial has been received, flow continues to block 122. If the T_2 count does not exceed the threshold, threshold₂, in block 122, the flow continues back to block 116. If the T_2 count exceeds a threshold, threshold₂, in block 122, the base station generates a surrogate PTT_off indication to send to the communications manager, block 134 thereby freeing the system for use by other remote units and flow ends in block 138. If the link activity is detected in block 116, the T_2 count is reset, block 126. Block 130 asks if a denial of system talker privileges has been received. If a denial has been received, the flow ends in block 136. If no denial has been received, flow continues to block 116.

The mechanism deployed in blocks 106 and 116 to detect link activity may be the same or different. One example of a link detection mechanism is to count the average number of low rate frames received over a certain period. In this way, if background noise causes occasional higher rate frame, the lack of a valid continuous voice signal is still detected. In the preferred

embodiment, vocoder frames are transferred over the air at a rate of one per 20 msec. The mechanisms of blocks 106 and 116 may monitor 16 consecutive frames. If 15 out of 16 of the frames comprise eighth rate data, the link activity is not sufficient to indicate active use.

5 When the base station sends the communications manager the surrogate PTT_off indication, the communications manager may or may not be able to distinguish the surrogate indication from a PTT_off indication received directly from the remote unit. When the communications manager receives the surrogate PTT_off indication, it may respond by sending a denial
10 of system talker privileges to the remote unit. If the communications manager cannot distinguish between the surrogate PTT_off indication and a remote unit generated PTT_off indication, it may send the denial in response to every PTT_off indication that it receives. If it can distinguish between the two, the communications manager need only send a denial when a surrogate
15 PTT_off is received. In the preferred embodiment, the denial is sent on the reverse link traffic channel to the remote unit. In response to the denial, the remote unit may stop transmitting an active voice signal and either become inactive or enter a hanging state. The remote unit may respond by alerting the user or by taking corrective action.

20 Note what the flow chart shown in FIG. 2 operates to accomplish. The top loop, generally comprised of blocks 106, 108, 110, and 112, is concerned with the first scenario. The top loop monitors link activity until active voice or data communication is received. If the upper loop is exited, the lower loop, generally comprised of blocks 116, 118, 120, and 122, is concerned with the
25 second scenario. The lower loop continues to monitor the link activity of the incoming signal as the call progresses. Note that the threshold₁ and threshold₂ values need not be the same value. If they are selected as the same value, the loop collapses into a single loop. In a most general situation, threshold₁ has a smaller value than threshold₂. It is assumed that if a user
30 initially presses the push-to-talk button it is because he has something he wants to communicate. If he does not begin to communicate the message immediately it is probably because there has been an error or an intentional attempt to deadlock the system. Threshold₂ is longer because once the user has begun to speak, it is assumed he may pause during the speech. The
35 threshold₁ may have a value such as 5 - 10 seconds. The threshold₂ may have a value such as 10 - 20 seconds.

In the most general embodiment, the present invention is a method and apparatus for monitoring the absence of voice or data information in a push-to-talk system to prevent system deadlock. Of course the general

principles illustrated in FIG. 2 could be applied to a great many different embodiments. For example, the lowest rate frame may not be an eighth rate frame in an alternative embodiment. The present invention would also prevent deadlock if a microphone or other voice path component failed in the remote unit such that no voice signal was transmitted from the remote unit.

There are many variations and implementations which fall within the scope of the present invention. An implementation may comprise all the elements of the present invention and yet not follow exactly the flow charts of FIG. 2. For example, explicit in the above diagram is the fact that if at any time the base station receives a PTT_off indication from the remote unit, the entire flow chart process is aborted. Obviously the same effect could be achieved by using interrupts rather than periodic inquiry. Also the blocks may be reordered within the flow without effecting the operation of the system. Also note that even though the text herein refers to 'remote' units, some of the units may be wireline units.

The previous description of the preferred embodiments is provided to enable any person skilled in the art to make or use the present invention. The various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without the use of the inventive faculty. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

WE CLAIM:

CLAIMS

1. A method for preventing deadlock in a dispatch system
2 wherein a set of remote units communicate with each other by broadcasting
one at a time to the group, comprising the steps of:
4 receiving at a base station from a remote unit a request to be a system
talker;
6 receiving at said base station from a communications manager a grant
to be system talker for said remote unit;
8 monitoring a series of data from said remote unit at said base station
to detect voice activity; and
10 sending by said base station to said communications manager a
surrogate request to desist as said system talker for said remote unit if said
12 voice activity falls below a threshold.

2. A method of preventing deadlock in a push-to-talk system where
2 a single remote unit at a time may be designated as a system talker,
comprising the steps of:
4 monitoring link activity from a remote unit that is currently
designated as said system talker; and
6 sending a denial of system talker privileges to said remote unit if a lack
of link activity is detected.

3. The method of Claim 2 wherein said step of monitoring
2 comprises the steps of:
examining a spectral content of a signal received from said remote
4 unit;
comparing said spectral content to a first predetermined threshold; and
6 determining a lack of link activity if said spectral content is less than
said first predetermined threshold.

4. The method of Claim 2 wherein a signal received from said
2 remote unit comprises digital data and wherein said step of examining
comprises the steps of:
4 examining transitions between logic states of "1" and "0" in said digital
data; and
6 determining that said lack of link activity exists if an average number
of said transitions falls below a first predetermined threshold.

2 5. The method of Claim 2 wherein a signal received from said
remote unit comprises digital data and wherein said step of monitoring
further comprises the steps of:

4 determining an average number of occurrences of the logic state
of "1" in said digital data as compared to a total amount of digital data
6 received; and

8 determining said lack of link activity to be present if said average
number of occurrences is below a first threshold or above a second
threshold.

2 6. The method of Claim 2 wherein a signal from said remote unit
comprises variable rate data organized in frames, each frame having one of a
set of preselected data rates further comprising the step of evaluating said
4 frames to determine said lack of link activity.

2 7. The method of Claim 2 wherein a signal from said remote unit
comprises variable rate data organized in frames, each frame having one of a
set of preselected data rates and wherein said step of monitoring further
4 comprises the steps of:

6 determining an average number of frames received from said
remote unit at a lowest one of said set of preselected data rates; and

8 determining said lack of link activity to be present if said average
number of frames exceeds a first threshold for a first amount of time.

2 8. The method of Claim 7 wherein said step of monitoring further
comprises the steps of:

4 detecting an initial presence of link activity if a number of frames
is received at a rate other than said lowest one of said set of preselected
data rates; and

6 determining said lack of link activity to be present after detecting
said initial presence of link activity if said average number of frames
8 exceeds a second threshold for a second amount of time.

2 9. The method of Claim 8 wherein said second amount of time is
greater than said first amount of time.

10. A method of preventing deadlock in a dispatch system
2 comprising the steps of:

4 establishing a communications resource for use by a first remote
unit as a system talker;

6 receiving a request for a system talker privilege from said first
remote unit;

8 granting said system talker privilege to said first remote unit;

receiving a traffic signal from said first remote unit;

monitoring link activity on said traffic signal; and

10 denying said system talker privilege to said first remote unit if
said link becomes inactive.

11. The method of Claim 10 wherein the link is defined as inactive
2 upon said link activity decreasing below a predetermined level.

12. The method of Claim 10 further comprising the step of reserving
2 said communications resource for use by said first remote unit subject to a
subsequent request to become said system talker without requiring
4 repetition of said step of establishing said communication resource.

13. The method of Claim 10 wherein said traffic signal is a code
2 division multiple access signal.

14. The method of Claim 10 wherein said traffic signal is a time
2 division multiple access signal.

15. The method of Claim 10 wherein said step of denying said
2 system talker privilege to said first remote unit comprises the steps of:

4 sending, from a base station to a communications manager, a
surrogate request to terminate said system talker privilege to said first
remote unit;

6 responding to said surrogate request by sending a denial of
system talker privilege from said communications manager to said
8 base station; and

10 sending said denial of system talker privilege from said base
station to said first remote unit.

16. The method of Claim 15 further comprising the steps of:

2 sending an off indication, requesting release from said system
talker privilege, from said first remote unit to said base station;

4 sending a request to terminate said system talker privileges of
said first remote unit from said base station to said communications
6 manager in response to said off indication; and

8 sending said denial indication from said communications
manager to said base station.

17. The method of Claim 10 wherein said traffic signal from said first
2 remote unit comprises variable rate data organized in frames, each frame
having one of a set of preselected data rates, wherein said step of monitoring
4 further comprises the steps of:

6 determining, at said base station, an average number of frames in
said traffic signal at a lowest one of said set of preselected data rates;
and

8 determining that said link activity has fallen below said
predetermined level if said average number of frames exceeds a first
10 threshold for a first amount of time.

18. The method of Claim 17 wherein said step of monitoring further
2 comprises the steps of:

4 detecting, at said base station, an initial presence of said link
activity; and

6 determining that said link activity has fallen below said
predetermined level after detecting said initial presence of said link
activity when said average number of frames exceeds a second
8 threshold for a second amount of time.

19. The method of Claim 18 wherein said step of detecting said initial
2 presence of link activity comprises the step of detecting, in said traffic
channel, a number of frames at a data rate other than said lowest one of said
4 data rates.

20. A system for preventing deadlock in a dispatch system which is
2 configured to serve remote units, said system comprising:

4 a remote unit, designated as a system talker, that sends variable
rate data for broadcast transmission to a set of other remote units;

6 a base station that receives said variable rate data, monitors said
variable rate data to detect link activity and broadcasts said variable
rate data to said set of other remote units; and

8 a communications manager that receives a surrogate remote
unit release indication signal from said base station if said link activity
10 falls below a predetermined level and that issues a release indication
signal to said base station for transmission to said remote unit, so as to
12 command said remote unit to cease transmission of said variable rate
data.

21. An apparatus that prevents deadlock in a push-to-talk system
2 where a single remote unit may be designated as a system talker at any one
point in time comprising:

4 means for monitoring link activity from a first remote unit that
is currently designated said system talker; and

6 means for sending a denial of system talker privileges to said first
remote unit if a lack of link activity is detected.

22. The apparatus of Claim 21 wherein a signal from said first
2 remote unit comprises variable rate data organized in frames, each frame
having one of a set of preselected data rates wherein said means for
4 monitoring further comprises:

6 means for determining an average number of frames received
from said first remote unit at a lowest one of said set of preselected
data rates; and

8 means for detecting said average number of frames exceeding a
first threshold for a first amount of time as said lack of link activity.

23. The apparatus of Claim 21 wherein said means for monitoring
2 further comprises:

4 means for detecting an initial presence of link activity if a
number of frames is received at a rate other than said lowest one of
said set of preselected data rates; and

6 means for determining said lack of link activity after detecting
said initial presence of link activity if said average number of frames
8 exceeds a second threshold for a second amount of time.

1/2




FIG. 1

2/2





FIG. 2



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/28, 7/38		A3	(11) International Publication Number: WO 97/50266
			(43) International Publication Date: 31 December 1997 (31.12.97)
(21) International Application Number: PCT/US97/10831		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 23 June 1997 (23.06.97)			
(30) Priority Data: 669,778 26 June 1996 (26.06.96) US			
(71) Applicant: QUALCOMM INCORPORATED [US/US]; 6455 Lusk Boulevard, San Diego, CA 92121 (US).			
(72) Inventors: YAO, Yu-Dong; 10923 Caminito Alvarez, San Diego, CA 92126 (US). GROB, Matthew, S.; 2757 Bordeaux Avenue, La Jolla, CA 92037 (US).			
(74) Agent: OGROD, Gregory, D.; Qualcomm Incorporated, 6455 Lusk Boulevard, San Diego, CA 92121 (US).			
		Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
		(88) Date of publication of the international search report: 26 February 1998 (26.02.98)	

(54) Title: METHOD AND APPARATUS FOR MONITORING LINK ACTIVITY TO PREVENT SYSTEM DEADLOCK IN A DISPATCH SYSTEM



(57) Abstract

A method and apparatus to prevent system deadlock in a dispatch system by monitoring link activity is described. The dispatch system is comprised of a set of remote units (10, 20, 22) which communicate with each other by broadcasting one at a time to the group. A remote unit (10) communicates with the other remote units through at least one base station (44). A communications manager (40) grants a remote unit (10) to be the exclusive system talker upon request through the base station servicing the requesting remote unit (44). The base station (44) monitors a series of data from the remote unit designated as the system talker (10) to detect voice activity. The base station (44) sends a surrogate request to the communications manager (40) to relinquish the system talker privilege if the voice activity falls below a predetermined threshold.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/10831

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H0407/28 H0407/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q H04J H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
X Y A	US RE32789 E (LYNK JR CHARLES NELSON ET AL) 22 November 1988 see column 6, line 4 - column 7, line 24 ---	2,3,10, 11,21 12 1,15,20
Y	WO 96 00482 A (NOKIA TELECOMMUNICATIONS OY ;HIPPELAEINEN LEO (FI)) 4 January 1996 see page 7, line 13 - page 10, line 23 see figure 3 ---	12
A	WO 94 30026 A (MOTOROLA INC) 22 December 1994 see page 4, line 15 - page 7, line 2 --- -/--	1,2,6-8, 13-15, 17-20, 22,23

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
15 December 1997	23/12/1997
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Roberti, V

INTERNATIONAL SEARCH REPORT

Inventor's Name: International Application No.

PCT/US 97/10831

C. (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 400 361 A (BRAUNS GREGORY T ET AL) 21 March 1995 see column 2, line 10-63 see column 3, line 37-57	2.4.5
A	WO 93 07685 A (NOKIA TELECOMMUNICATIONS OY) 15 April 1993 see page 4, line 20 - page 5, line 32	2.3

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/10831

Patent document cited in search report	Publication date	Patent family members:	Publication date
US RE32789 E	22-11-88	US 4012597 A	15-03-77
		CA 1067988 A	11-12-79
		DE 2652967 A	07-07-77
		FR 2332664 A	17-06-77
		GB 1566305 A	30-04-80
		JP 1193496 C	12-03-84
		JP 52065602 A	31-05-77
		JP 58026863 B	06-06-83
		JP 1459146 C	28-09-88
		JP 58136146 A	13-08-83
		JP 63000975 B	09-01-88
		JP 1309726 C	26-03-86
		JP 58136147 A	13-08-83
		JP 60027215 B	27-06-85
		NL 7613116 A,B.	26-05-77
WO 9600482 A	04-01-96	FI 943087 A	28-12-95
		AU 2793795 A	19-01-96
		CN 1130011 A	28-08-96
		EP 0715800 A	12-06-96
		JP 9502590 T	11-03-97
WO 9430026 A	22-12-94	EP 0654202 A	24-05-95
US 5400361 A	21-03-95	US 5506870 A	09-04-96
WO 9307685 A	15-04-93	FI 91202 C	25-05-94
		AT 146024 T	15-12-96
		AU 653864 B	13-10-94
		AU 2647092 A	03-05-93
		DE 69215658 D	16-01-97
		DE 69215658 T	28-05-97
		EP 0560962 A	22-09-93
		US 5375253 A	20-12-94

This Page Blank (uspto)